

Cheyenne

Many Native American tribes produced leather by wet-scraping hides in a wood ash and water solution, while other tribes practiced dry-scraping. Both trends are tied to modern day tanning techniques, which we salute in our Cheyenne article. Aniline dyed, vacuum dried and gently milled, Cheyenne has a frontier quality that's at once both edgy and refined. A smooth, soft hand and mild sheen serve as icing on the cake.

Hide Origin	Europe
Country Finished	Italy
Average Hide Size	50-52 SF
Thickness	1.0-1.2 mm
Dye Method	Aniline
Finish	Spilltop® Water Resistance
Light Fastness (EN ISO 105-B02)	4
Cigarette Ignition Resistance (NFPA 260)	Class 1
IMO 2010 Part 8 [IMO RES. A652 (16)]	
Smoldering Cigarette (3.1)	Passes
Propane Flame (3.2)	Passes
Spilltop Water Resistance	
AATCC Test Method 22-2010	95 (ISO 4)



SPILLTOP leather is rated 90-100 with minimal-to-no sticking or wetting of the article's surface.

- 100 – No sticking or wetting of specimen face
- 90 – Slight random sticking or wetting of specimen face
- 80 – Wetting of specimen face at spray points
- 70 – Partial wetting of specimen face beyond spray points
- 50 – Complete wetting of the entire specimen face beyond spray points
- 0 – Complete wetting of the entire face of the specimen

CARE & CLEANING

Routine dusting or vacuuming is encouraged. To add luster and longevity, rotate article periodically and avoid direct sunlight. For spills, gently blot area with cloth or sponge without applying force. If needed, dampen cloth or sponge with warm water. Do not use a hair dryer. Do not use saddle soap, solvents, oils, polishes, varnishes, detergents, bleach or ammonia.